



Product Data Sheet

■ FX™-22

Carthage Mills' FX™-22 is a woven slit film geotextile of 100% polypropylene yarns. This product features high tensile strengths at low elongations (high modulus) making it ideal for soil separation and stabilization applications.

PROPERTY	TEST METHOD	DATA	
		METRIC	ENGLISH
<input type="checkbox"/> Mechanical			
Grab Tensile	ASTM D 4632	485 x 355 N	110 x 80 lbs
Grab Tensile Elongation			
Wide Width Tensile	ASTM D 4595		n/a
Wide Width Elongation			n/a
Mullen Burst	ASTM D 3786	1510 kPa	220 psi
Puncture	ASTM D 4833	n/a	
Trapezoidal Tear	ASTM D 4533	200 x 155 N	45 x 35 lbs
<input type="checkbox"/> Endurance			
UV Resistance	ASTM D 4355	90% @ 500 hrs	
<input type="checkbox"/> Hydraulics / Filtration			
Apparent Opening Size (AOS)	ASTM D 4751	0.300 mm	50 US Std. Sieve
Percent Open Area	CW-02215	< 1%	
Permittivity	ASTM D 4491	0.02 sec ⁻¹	
Permeability		.001 cm/sec	
Flow Rate		80 l/min/m ²	2 gpm/ft ²
<input type="checkbox"/> Physical / Dimensional			
Mass Per Unit Area	ASTM D 5261	90 g/m ²	2.5 oz/yd ²
Standard Roll Sizes / Packaging (Special sizes, packaging and fabrication are available.)	Measured (Typical)	3.81 m x 131.76 m 502 m ² 61 kg 24.1 cm diameter	12.5 ft x 432 ft 600 yd ² 135 lbs 9.5 in. diameter

- Unless otherwise noted, all properties reported are Minimum Average Roll Values (MARV), and are calculated as the typical minus two standard deviations. Statistically, it yields a 97.7% degree of confidence that any sample taken during quality assurance testing will exceed the value reported.
- The properties reported above are effective 02/01/03 and are subject to change without notice.

Seller makes no warranty, expressed or implied, concerning the product furnished hereunder other than at the time of delivery it shall be of the quality and specification stated herein. Any implied warranty of fitness for a particular purpose is expressly excluded, and, to the extent that it is contrary to the foregoing sentence, any implied warranty of merchantability is expressly excluded. Any recommendations made by seller concerning the uses or applications of said product are believed reliable and seller makes no warranty of results to be obtained. If the product does not meet Carthage Mills current published specifications, and the customer gives notice to Carthage Mills before installing the product, then Carthage Mills will replace the product without charge or refund the purchase price.