

Form Oil VOC

Description

A low cost blend of petroleum based organic chemicals which prevent adhesion of concrete to forms. V.O.C. compliant.

physician. If splashed in eyes, wash repeatedly with clean water and call physician. Keep away from heat, sparks and open flame.

Recommended Safety Equipment:

Rubber gloves, goggles and if applied in areas of poor or inadequate ventilation, use mine safety appliances, mask and canister:

Organic Vapor Mask
(No. 457081)

Organic Vapor Canister
(No. 77705GAM)

Threshold Limit Value: 100 PPM.

Ventilation system should be capable of exchanging total air volume in application area in 30 minutes or less.

Avoid hazards by following all precautions found in the Material Safety Data Sheet (MSDS), product labels and technical literature. Please read this information prior to using the product.

V.O.C. Content

Less than 450 g/l. Complies with Federal V.O.C. standards for Form Release Agents. Do not thin or dilute.

Manufacturer

Conspec

636 S. 66th Terrace

Kansas City, Kansas 66111

Customer Service (800) 348-7351

Technical Service (877) CONSPEC

Use

Form Oil VOC is used to release concrete from steel, wood and plastic forms.

Benefits

- V.O.C. compliant-Federal standards
- Creates a positive barrier to which concrete cannot adhere
- Will not cause concrete dusting - concrete build-up is reduced
- Contains a positive rust inhibitor - a light coat on steel forms upon stripping will prevent rust for weeks
- Is non-staining
- Will not soften concrete
- Eliminates any need to sandblast concrete before plastering, etc.

Architectural Specifications

Form Release Agent: All cleaned concrete form faces should be coated with a chemical release agent that is non-staining and that will not inhibit the natural bonding characteristics of secondary toppings or coatings, caulks or sealants. Approved product: Conspec Form Oil VOC or approved equivalent.

Application

Form Oil VOC is effective when applied at a rate of 1000-1500 square feet per gallon (24.5-36.8 m²/L).

Packaging

55 gallon drums (208.2 L)

5 gallon pails (18.9 L)

1 gallon cans (6 to a case)(3.8 L)

Limitations/Precautions

Combustible...Contains petroleum distillates. Keep out of reach of children. Do not take internally. Do not breathe vapors. Avoid prolonged contact with skin. If swallowed, do not induce vomiting - call

Warranty

Conspec warrants, for 12 months from the date of manufacture or for the duration of the published product shelf life, whichever is less, that at the time of shipment by Conspec, the product is free of manufacturing defects and conforms to Conspec's published specifications in force on the date of acceptance by Conspec of the order. Conspec shall only be liable under this warranty if the material has been applied, used, and stored in accordance with Conspec's instructions in this technical data sheet. The purchaser must examine the product when received and promptly notify Conspec in writing of any non-conformity before the product is used, or no later than 30 days after such non-conformity is first discovered. If Conspec, in its sole discretion, determines that the product breached the above warranty, it will, in its sole discretion, replace the non-conforming product, refund the purchase price or issue a credit in the amount of the purchase price. This is the sole and exclusive remedy for breach of this warranty. Only a Conspec officer is authorized to modify this warranty. The sales information on the Conspec website and received by the customer during the sales process does not supersede this warranty and the specifications of the product in force on the date of sale. **THE FOREGOING WARRANTY SHALL BE EXCLUSIVE AND IN LIEU OF ANY OTHER WARRANTY,**

EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND ALL OTHER WARRANTIES OTHERWISE ARISING BY OPERATION OF LAW, COURSE OF DEALING, CUSTOM, TRADE OR OTHERWISE.

Limitation of Liability

Conspec shall not be liable in contract or in tort (including, without limitation, negligence, strict liability or otherwise) for loss of sales, revenues or profits; cost of capital or funds; business interruption or cost of downtime, loss of use, damage to or loss of use of other property (real or personal); failure to realize expected savings; frustration of economic or business expectations; claims by third parties (other than for bodily injury), or economic losses of any kind; or for any special, incidental, indirect, consequential, punitive or exemplary damages arising in any way out of the performance of, or failure to perform, this Agreement, even if Conspec could foresee or has been advised of the possibility of such damages. The Parties expressly agree that these limitations on damages are allocations of risk constituting, in part, the consideration for this agreement, and also that such limitations shall survive the determination of any court of competent jurisdiction that any remedy provided in these terms or available at law fails of its essential purpose.

Storage

Form Oil VOC should be stored in tightly sealed original factory containers. Store in a horizontal position to prevent moisture accumulation on the drum head.

Technical Services

Complete technical and specification services are available from the manufacturer and their authorized representatives and distributors.

Filing System

Additional literature and the material Safety Data Sheet can be obtained from Conspec upon request.