
SECTION 3 - HAZARDS IDENTIFICATION

EFFECTS OF OVEREXPOSURE - INGESTION: Moderately toxic.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No known components of this product are listed as known or suspected carcinogens per NIOSH, NTP, IARC, or OSHA. This product contains solvents. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") may be harmful or fatal.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION INGESTION

SECTION 4 - FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 110 F
(TAGLIABUE CLOSED CUP)

LOWER EXPLOSIVE LIMIT: 0.9 %
UPPER EXPLOSIVE LIMIT: 15.3 %

AUTOIGNITION TEMPERATURE: N/D

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: Vapors can travel to a source of ignition and flash back. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. Solid stream of water or foam may cause frothing.

SPECIAL FIREFIGHTING PROCEDURES: Containers exposed to fire should be kept cool with water spray. Containers can build up pressure if exposed to heat

(Continued on Page 3)

SECTION 5 - FIRE FIGHTING MEASURES

(fire). As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

SECTION 7 - HANDLING AND STORAGE

HANDLING: Keep out of reach of children. Ground and bound containers when transferring material.

STORAGE: Keep container closed when not in use.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGIENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Avoid breathing vapors from heated material. Avoid contact with eyes, skin, and clothing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

BOILING RANGE	: 308 - 401 F	VAPOR DENSITY	: Is heavier than air
ODOR	: Slight paint	ODOR THRESHOLD	: N/D
APPEARANCE	: Milky liquid	EVAPORATION RATE:	Is slower than Butyl Acetate
SOLUBILITY IN H2O	: Negligible <0.1%	SPECIFIC GRAVITY:	1.0000
FREEZE POINT	: N/D	pH @ 0.0 %	: N/D
VAPOR PRESSURE	: N/D	VISCOSITY	: N/D
PHYSICAL STATE	: Liquid		

(Continued on Page 4)

 SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

COEFFICIENT OF WATER/OIL DISTRIBUTION: N/D

(See Section 16 for abbreviation legend)

 SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Long term exposure to elevated temperatures.

INCOMPATIBILITY: Strong bases or oxidants. Strong Lewis or mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Acrid fumes. Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

 SECTION 11 - TOXICOLOGICAL PROPERTIES

PRODUCT DERMAL LD50: No Information PRODUCT ORAL LD50: No Information
 PRODUCT LC50: No Information

COMPONENT TOXICOLOGICAL INFORMATION:

----- CHEMICAL NAME -----	-- DERMAL LD50 --	--- ORAL LD50 ---	----- LC50 -----
ethylene glycol	9530 uL/kg	4700 mg/kg	10876 mg/kg
Naphtha-light aromatic	>4 ml/kg	4.7 g/kg	>3670 ppm/8H
1,2,4 Trimethyl Benzene	No Information	12.7 gm/kg	18 gm/m3/4H

 SECTION 12 - ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: No Information.

 SECTION 13 - DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

 SECTION 14 - TRANSPORTATION INFORMATION

DOT PROPER SHIPPING NAME: Combustible Liquid, nos

DOT TECHNICAL NAME: Aromatic naphtha

DOT HAZARD CLASS: COMBUSTIBLE LIQUID

HAZARD SUBCLASS: N/A

(Continued on Page 5)

SECTION 14 - TRANSPORTATION INFORMATION

DOT UN/NA NUMBER: NA1993 PACKING GROUP: III RESP. GUIDE PAGE:
 DOT PLACARD AT: 1000 lbs
 DOT CLASS NUMBER: 3
 UN PROPER SHIPPING NAME: Paint
 UN HAZARD CLASS: FLAMMABLE LIQUID
 UN CLASS NUMBER: AIR 3 MARINE 3.3
 HAZARD SUBCLASS: AIR N/A MARINE N/A
 UN UN/NA NUMBER: UN1263 UN PACKING GROUP: AIR III MARINE III]
 UN PLACARD AT: N/A

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD FIRE HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME -----	CAS NUMBER	WT/WT %	IS LESS THAN
ethylene glycol	107-21-1		5.0 %
1,2,4 Trimethyl Benzene	95-63-6		5.0 %

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME -----	CAS NUMBER
Diethylene Glycol Monobutylether	112-34-5
dibutyl phthalate	84-74-2
cumene	98-82-8

(Continued on Page 6)

SECTION 15 - REGULATORY INFORMATION

CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

----- CHEMICAL NAME -----	CAS NUMBER
dioxane	123-91-1
ethylene oxide	75-21-8

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

SECTION 16 - OTHER INFORMATION

HMIS RATINGS - HEALTH: 2 FLAMMABILITY: 2 REACTIVITY: 0
PERSONAL PROTECTION: B

PREVIOUS MSDS REVISION DATE: 01/13/99

REASON FOR REVISION: Extinguishing media added.

VOLATILE ORGANIC COMPOUNDS (VOCS): 2.76 lbs/gal, 330 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,
N.D. - Not Determined

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of ChemRex's knowledge, or is obtained from sources believed by ChemRex to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. Chemrex assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, ChemRex assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

<END OF MSDS>

