

**EMACO R350CI**

Version 1.1

04/24/03

**1. COMPANY AND PRODUCT INFORMATION**

Company : ChemRex®  
 889 Valley Park Drive  
 SHAKOPEE, MN 55379 ,  
 Phone : 952-496-6000  
 Fax :  
 Emergency contact : 1-800-424-9300  
 Productname : EMACO R350CI  
 MSDS : 10219

2. HAZARDOUS INGREDIENTS:	CASNO	TLV	EXPOSURE LIMITS*			CONTENT
			STEL	PEL		
Silica, Crystalline Quartz **	14808-60-7	***	None	****	30-60%	
Portland Cement	65997-15-1	10 mg/m3 (Respirable)	None	None	30-60%	

- \*) Refer to Section 7 for available LD/LC(50) Health Hazard Data.
- \*\*) Contains less than 0.1% w/w 53 micron or smaller Crystalline Quartz.
- \*\*\*) 0.1 mg/m3 respirable quartz
- \*\*\*\*) 10 mg/m3 divided by %SiO2+2 (respirable quartz)

**3. PHYSICAL DATA:**

Boiling Point (oC):	N/Ap	Water/Oil Distribution	
Percent Volatile:	0	Coefficient:	N/Av
Freezing Point (oC):	N/Ap	Solubility in Water:	Slight
Vapor Pressure mmHg @20(oC):	N/Av	Specific Gravity:	N/Av
Vapor Density:	> Air	pH:	N/Ap
Odor Threshold:	N/Av	Evaporation Rate:	N/Av
Appearance: Off-white coarse powder		Odor: Odorless	
N/Av = Not Available	N/Ap = Not Applicable		ca. = Approximate

**4. FIRE AND EXPLOSION HAZARD DATA:** HMIS Hazard Rating No. 0 (Minimal)

Flash Point: Non-flammable Method: Not Applicable

Auto-Ignition Temp.: Not Applicable

**EMACO R350CI**

Version 1.1

04/24/03

**4. FIRE AND EXPLOSION HAZARD DATA:** (cont'd)

Limits of Flammability: LEL: Non-flammable UEL: Non-flammable

Extinguishing Media: This material is non-flammable. Use extinguishing media suitable for surrounding fires.

Special Fire & Unusual Hazards: None.

**5. REACTIVITY DATA:** HMIS Hazard Rating No. 0 (Minimal)

Stability: Stable. Not sensitive to mechanical impact.

Incompatibility: Strong mineral acids.

Hazardous Decomposition Products: None known.

Hazardous Polymerization: Will not occur.

**6. ENVIRONMENTAL AND DISPOSAL INFORMATION:**

Action to Take for Spills/Leaks: No special procedures are required for clean-up of spills or leaks of this material. Sweep up and return for reuse or discard. Landfill at agency approved waste-disposal facilities.

Waste Disposal Method: Does not contain hazardous chemicals as defined in 40 CFR 260. Handle disposal of waste material in manner which complies with local, state, province and federal regulation. Landfill agency approved waste-disposal facilities.

**7. HEALTH HAZARD DATA:** HMIS Hazard Rating No. 3 (Serious)

PRIMARY ROUTE OF ENTRY: Inhalation

**Effects Of Overexposure**

Inhalation: Inhalation of nuisance dust can cause coughing and labored breathing

Eyes: Abrasive action may cause severe irritation and possible injury. In combination with water may cause severe irritation and possibly burns.

Skin Contact: Abrasive action may cause slight to moderate irritation. In combination with water, repeated or prolonged dermal exposure may cause moderate to severe alkali burns.

Skin Absorption: Does not absorb through skin.

Ingestion: Not likely source of entry due to physical nature of material.

**EMACO R350CI**

Version 1.1

04/24/03

7. **HEALTH HAZARD DATA:** (cont'd)Chronic

Materials are not known mutagenic, teratogenic, or reproductive health hazards. Repeated inhalation of respiratory silica in excess of the TLV over extended periods can result in irreversible fibrosis of the lungs (silicosis). An IARC evaluation concluded that there is sufficient evidence (Group I) that crystalline silica may be carcinogenic to humans.

8. **FIRST AID:**Inhalation:

Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek medical attention.

Eyes:  
medical attention.

Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek

Skin:

Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.

Ingestion:

Do **NOT** induce vomiting; give large quantities of water; get immediate medical attention. If vomiting occurs spontaneously, keep head below hips to prevent aspiration of liquids into lungs. Do **NOT** give anything by mouth to an unconscious person.

9. **SPECIAL PROTECTION INFORMATION:**

Ventilation: Ventilation is recommended. Air movement must be designed to insure turnover at all locations in work area to avoid build up of airborne dust concentrations.

Personal Protection Equipment: Do NOT wear contact lenses when working with this material. Use safety glasses with side shields and Rubber/Latex gloves. Selection of specific items such as boots and apron will depend on operation. Wear respirator protection whenever airborne concentrations exceed TLV ceilings or TWA, use NIOSH/OSHA approved respirators equipped with a dust cartridge for listed hazard.

Confined spaces, rooms, or tanks are areas where concern for TLV's is especially important. Reference OSHA Regulation CFR 29 1910.134 for recommended respiratory protection.

10. **ADDITIONAL INFORMATION:**Average Shelf Life:

Refer to Product Data Sheet.

Special Instructions:

Store in cool, dry place.

**EMACO R350CI**

Version 1.1

04/24/03

10. **ADDITIONAL INFORMATION:** (cont'd)**REGULATORY INFORMATION:**Title III Section 302: No reportable chemicals.Title III Section 311/312: Health hazard: Immediate  
Delayed  
Physical hazard: NoneTitle III Section 313: No reportable materials.State: California This product contains a chemical known to the state of California to cause cancer.

Silica, Crystalline Quartz (Respirable) 14808-60-7 &lt; 0.1 %

WHMIS Classification: Class D, Div. 2, Sub A;  
Class D, Div. 2, Sub B  
Class ECanadian Domestic Substance List: All chemicals are listed.**TRANSPORTATION**

National Motor Freight Classification (NMFC): 42130 Sub: - Class: 50

Description: CEMENT, HYDRAULIC

Emergency Response Guide Page No.: NOT APPLICABLE

DOT Reportable Quantity: NOT APPLICABLE

Proper Shipping Name: NOT REGULATED - USE NMFC DESCRIPTION

Marine Pollutant: NL

P = Moderate

PP = Severe

WS = Water Sheen

NL = Not Listed

ND = Not Determined

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the Manufacturer's knowledge, or is obtained from sources believed by the Manufacturer to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The Manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the Manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.