



|                                    |
|------------------------------------|
| SECTION 3 - HAZARDS IDENTIFICATION |
|------------------------------------|

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: May cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to mouth, throat and stomach.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: This product contains silicon dioxide [quartz] which has been listed as a suspected human carcinogen by NTP and IARC.

PRIMARY ROUTE(S) OF ENTRY: SKIN CONTACT INHALATION INGESTION EYE CONTACT

|                                |
|--------------------------------|
| SECTION 4 - FIRST AID MEASURES |
|--------------------------------|

FIRST AID - EYE CONTACT: Flush eye with water for 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, DO NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Should vomiting occur, be sure to keep victim's head below hips to avoid aspiration of vomitus into lungs.

|                                    |
|------------------------------------|
| SECTION 5 - FIRE FIGHTING MEASURES |
|------------------------------------|

FLASH POINT: >200 F

LOWER EXPLOSIVE LIMIT: N.E.

UPPER EXPLOSIVE LIMIT: N.E.

AUTOIGNITION TEMPERATURE: N.E.

EXTINGUISHING MEDIA: CO2 DRY CHEMICAL WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information.

SPECIAL FIREFIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

(Continued on Page 3)

---

|   |
|---|
| SECTION 6 - ACCIDENTAL RELEASE MEASURES |
|---|

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Absorb spill with inert material (e.g. dry sand or earth), then place in a chemical waste container. Repeat sorbent/sweep cycle until the spill has dried up. Avoid runoff into storm sewers and ditches which lead to waterways.

|                                  |
|----------------------------------|
| SECTION 7 - HANDLING AND STORAGE |
|----------------------------------|

HANDLING: Use only in a well ventilated area. Keep out of reach of children. If user operations generate dust, fume, or mist, use ventilation to keep exposure to airborne contaminants below the exposure limit.

STORAGE: Keep container closed when not in use.

|   |
|---|
| SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION |
|---|

ENGINEERING CONTROLS: Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

RESPIRATORY PROTECTION: Wear NIOSH/MSHA approved respiratory protection when the product is mixed or applied in a poorly ventilated area or if workplace levels of ingredients exceed the TLV. Follow applicable federal, state, and local regulations.

OTHER PROTECTIVE EQUIPMENT: Where contact is likely, wear chemical resistant gloves, chemical safety goggles with a face shield, and clean protective clothing to cover arms and legs to keep exposure to a minimum.

HYGIENIC PRACTICES: Do not take internally. Wash thoroughly after handling. Avoid contact with eyes, skin, and clothing.

|  |
|--|
| SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES |
|--|

|   |                 |                   |                              |
|---|-----------------|-------------------|------------------------------|
| BOILING RANGE                               | : N.A.          | VAPOR DENSITY     | : Is heavier than air        |
| ODOR  | : Slight sweet  | ODOR THRESHOLD    | : N.E.                       |
| APPEARANCE                                  | : Opaque liquid | EVAPORATION RATE: | Is slower than Butyl Acetate |
| SOLUBILITY IN H2O                           | : Soluble       | SPECIFIC GRAVITY: | 1.6000                       |
| FREEZE POINT                                | : N.E.          | pH @ 100.0 %      | : 9.5 - 10                   |
| VAPOR PRESSURE                              | : N.E.          | VISCOSITY         | : N.E.                       |
| PHYSICAL STATE                              | : Liquid        |                   |                              |
| COEFFICIENT OF WATER/OIL DISTRIBUTION: N.E. |                 |                   |                              |

(See Section 16 for abbreviation legend)

(Continued on Page 4)

|                                       |
|---------------------------------------|
| SECTION 10 - STABILITY AND REACTIVITY |
|---------------------------------------|

CONDITIONS TO AVOID: Long term exposure to elevated temperatures.

INCOMPATIBILITY: Strong bases or oxidants. Strong Lewis or mineral acids.

HAZARDOUS DECOMPOSITION PRODUCTS: Acrid fumes. Oxides of carbon.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

|                                       |
|---------------------------------------|
| SECTION 11 - TOXICOLOGICAL PROPERTIES |
|---------------------------------------|

PRODUCT DERMAL LD50: No Information      PRODUCT ORAL LD50: No Information

PRODUCT LC50: No Information

COMPONENT TOXICOLOGICAL INFORMATION:

| ---- CHEMICAL NAME ---- | -- DERMAL LD50 -- | --- ORAL LD50 --- | ---- LC50 ---- |
|-------------------------|-------------------|-------------------|----------------|
| Silica, precipitated    | No Information    | No Information    | No Information |
| mica                    | No Information    | No Information    | No Information |
| Limestone, Calcium carb | No Information    | 6450 mg/kg        | No Information |
| titanium dioxide        | No Information    | > 7500 mg/kg      | No Information |
| Calcium silicate        | No Information    | No Information    | No Information |
| Silica, quartz          | No Information    | No Information    | No Information |

|                                     |
|-------------------------------------|
| SECTION 12 - ECOLOGICAL INFORMATION |
|-------------------------------------|

ECOLOGICAL INFORMATION: No Information.

|                                      |
|--------------------------------------|
| SECTION 13 - DISPOSAL CONSIDERATIONS |
|--------------------------------------|

DISPOSAL METHOD: Review all local, state, and federal regulations concerning health and pollution for appropriate disposal procedures.

|   |
|---|
| SECTION 14 - TRANSPORTATION INFORMATION |
|---|

DOT PROPER SHIPPING NAME: Not Regulated

DOT TECHNICAL NAME: N.A.

DOT HAZARD CLASS: N.A.

HAZARD SUBCLASS: N.A.

DOT UN/NA NUMBER: N.A.

PACKING GROUP: N.A.

RESP. GUIDE PAGE:

DOT PLACARD AT: N.A.

(Continued on Page 5)

SECTION 14 - TRANSPORTATION INFORMATION

DOT CLASS NUMBER: N.A.

UN PROPER SHIPPING NAME: Not Regulated

UN HAZARD CLASS: N.A.

UN CLASS NUMBER: AIR N.A. MARINE N.A.

HAZARD SUBCLASS: AIR N.A. MARINE N.A.

UN UN/NA NUMBER: N.A. UN PACKING GROUP: AIR N.A. MARINE N.A.

UN PLACARD AT: N.A.

SECTION 15 - REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS -

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200)

CERCLA - SARA HAZARD CATEGORY:

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD CHRONIC HEALTH HAZARD

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

----- CHEMICAL NAME ----- CAS NUMBER WT/WT % IS LESS THAN  
No SARA Section 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

----- CHEMICAL NAME ----- CAS NUMBER  
None known.

U.S. STATE REGULATIONS: AS FOLLOWS -

|                                     |
|-------------------------------------|
| SECTION 15 - REGULATORY INFORMATION |
|-------------------------------------|

## CALIFORNIA PROPOSITION 65:

WARNING: The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm:

| ----- CHEMICAL NAME ----- | CAS NUMBER |
|---------------------------|------------|
| dioxane                   | 123-91-1   |
| Silica, quartz            | 14808-60-7 |
| inorganic lead            | 7439-92-1  |
| nickel                    | 7440-02-0  |
| Arsenic                   | 7440-38-2  |
| Cadmium                   | 7440-43-9  |
| ethylene oxide            | 75-21-8    |

INTERNATIONAL REGULATIONS: AS FOLLOWS -

CANADIAN WHMIS: This MSDS has been prepared in compliance with Controlled Product Regulations except for use of the 16 headings.

CANADIAN WHMIS CLASS: No information available.

|                                |
|--------------------------------|
| SECTION 16 - OTHER INFORMATION |
|--------------------------------|

HMIS RATINGS - HEALTH: 1 FLAMMABILITY: 1 REACTIVITY: 0  
PERSONAL PROTECTION: E

PREVIOUS MSDS REVISION DATE: 07/13/99

REASON FOR REVISION: New Format

VOLATILE ORGANIC COMPOUNDS (VOCS): 0.53 lbs/gal, 63 grams/ltr

LEGEND: N.A. - Not Applicable, N.E. - Not Established,  
N.D. - Not Determined

---

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of ChemRex's knowledge, or is obtained from sources believed by ChemRex to be accurate. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. Chemrex assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, ChemRex assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

---

<END OF MSDS>